

SAFETY DATA SHEET

Based upon Regulation (EC) No. 1907/2006, as amended by Regulation (EC) No. 453/2010

Soudafoam Gun Low Expansion

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Product name : Soudafoam Gun Low Expansion
Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1.2.1 Relevant identified uses

polyurethane

1.2.2 Uses advised against

No uses advised against known

1.3 Details of the supplier of the safety data sheet:

Supplier of the safety data sheet

SOUDAL N.V. Everdongenlaan 18-20 B-2300 Turnhout Tel: +32 14 42 42 31 Fax: +32 14 44 39 71 msds@soudal.com

Manufacturer of the product

SOUDAL N.V. Everdongenlaan 18-20 B-2300 Turnhout Tel: +32 14 42 42 31 Fax: +32 14 44 39 71 msds@soudal.com

1.4 Emergency telephone number:

24h/24h: +32 14 58 45 45 (BIG) (Telephone advice: English, French, German, Dutch)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

2.1.1 Classification according to Regulation EC No 1272/2008

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Aerosol	category 1	H222: Extremely flammable aerosol.
Carc.	category 2	H351: Suspected of causing cancer.
Acute Tox.	category 4	H332: Harmful if inhaled.
STOT RE	category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H335: May cause respiratory irritation.
Skin Irrit.	category 2	H315: Causes skin irritation.
Resp. Sens.	category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	category 1	H317: May cause an allergic skin reaction.

2.1.2 Classification according to Directive 67/548/EEC-1999/45/EC

Classified as dangerous in accordance with the criteria of Directives 67/548/EEC and 1999/45/EC

Carc. Cat. 3; R40 - Limited evidence of a carcinogenic effect

F+; R12 - Extremely flammable.

Xn; R20 - 48/20 - Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Xi; R36/37/38 - Irritating to eyes, respiratory system and skin.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

http://www.big.be

© BIG vzw

Reason for revision: 2.2 Revision number: 0401 Publication date: 2002-08-21 Date of revision: 2013-04-23

134-15960-383-er

Product number: 38450 1 / 15

R42/43 - May cause sensitisation by inhalation and skin contact.

2.2 Label elements:

Labelling according to Regulation EC No 1272/2008 (CLP)







Contains polymethylene polyphenyl isocyanate

	1 - 31 - 3 3
Signal word	Danger
H-statements	
H222	Extremely flammable aerosol.
H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs thr

H373 May cause damage to organs through prolonged or repeated exposure.
H319 Causes serious eye irritation.

H335 Causes serious eye irritation.
H335 May cause respiratory irritation.
Causes skin irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

P-statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.
Wear protective gloves and eye protection/face protection.

P260 Do not breathe vapours/mist.

P309 + P311 | IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
P410 + P412 | Protect from sunlight. Do no expose to temperatures exceeding 50 °C/ 122°F.
P501 | Dispose of contents/container to manufacturer/competent authority.

Supplemental information

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Labelling according to Directive 67/548/EEC-1999/45/EC (DSD/DPD) Labels





Extremely flammable

Contains: polymethylene polyphenyl isocyanate.

R-phrases

20	Halliful by illifalation
36/37/38	Irritating to eyes, respiratory system and skin
40	Limited evidence of a carcinogenic effect

Harmful by inhalatio

42/43 May cause sensitisation by inhalation and skin contact

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

S-phrases

Reason for revision: 2.2

02 Keep out of the reach of children

16 Keep away from sources of ignition - No smoking

23 Do not breathe spray

36/37 Wear suitable protective clothing and gloves

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)

51 Use only in well-ventilated areas

(63) (In case of accident by inhalation: remove casualty to fresh air and keep at rest)

Additional recommendations

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Revision number: 0401 Product number: 38450 2 / 15

Publication date: 2002-08-21 Date of revision: 2013-04-23

Contains isocyanates. See information supplied by the manufacturer.

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards:

CLP

May be ignited by sparks

Gas/vapour spreads at floor level: ignition hazard

Aerosol may explode under the effect of heat

May be ignited by sparks

Gas/vapour spreads at floor level: ignition hazard Aerosol may explode under the effect of heat

SECTION 3: Composition/information on ingredients

3.1 Substances:

DSD/DPD

Not applicable

3.2 Mixtures:

Name (REACH Registration No)	CAS No EC No	Conc. (C)	Classification according to DSD/DPD	Classification according to CLP	Note	Remark
tris(2-chloro-1-methylethyl) phospha (01-2119447716-31)	13674-84-5 237-158-7	1% <c<25%< td=""><td>Xn; R22</td><td>Acute Tox. 4; H302</td><td>(1)(10)</td><td>Constituent</td></c<25%<>	Xn; R22	Acute Tox. 4; H302	(1)(10)	Constituent
polymethylene polyphenyl isocy <mark>anal</mark> (-)	te 9016-87-9	C>25%	Xi; R36/37/38 R42/43	Carc. 2; H351 Acute Tox. 4; H332 STOT RE 2; H373 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317	(1)(2)(10)	Polymer
propane (-)	74-98-6 200-827-9	1% <c<10%< td=""><td>F+; R12</td><td>Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280</td><td>(1)(2)(10)</td><td>Propellant</td></c<10%<>	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
isobutane (-)	75-28-5 200-857-2	1% <c<10%< td=""><td>F+; R12</td><td>Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280</td><td>(1)(2)(10)</td><td>Propellant</td></c<10%<>	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
dimethyl ether (01-2119472128 <mark>-37)</mark>	115-10-6 204-065-8	1% <c<10%< td=""><td>F+; R12</td><td>Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280</td><td>(1)(2)(10)</td><td>Propellant</td></c<10%<>	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
(1,3-butadiene, conc<0.1%) (-)						

⁽¹⁾ For R-phrases and H-statements in full: see heading 16

SECTION 4: First aid measures

4.1 Description of first aid measures:

General:

GENERAL. Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

Reason for revision: 2.2 Publication date: 2002-08-21
Date of revision: 2013-04-23

Revision number: 0401 Product number: 38450 3 / 15

⁽²⁾ Substance with a Community workplace exposure limit

⁽¹⁰⁾ Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

4.2 Most important symptoms and effects, both acute and delayed:

4.2.1 Acute symptoms

After inhalation:

Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Runny nose. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible inflammation of the respiratory tract. Risk of lung oedema. Respiratory difficulties.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue. Lacrimation.

After ingestion:

Not applicable.

4.2.2 Delayed symptoms

No effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

5.1.1 Suitable extinguishing media:

Quantities of water. Polyvalent foam. BC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known.

5.2 Special hazards arising from the substance or mixture:

On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide). May polymerize on exposure to temperature rise. On heating: release of toxic/combustible gases/vapours (hydrogen cyanide).

5.3 Advice for firefighters:

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Dilute toxic gases with water spray.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Stop engines and no smoking. No naked flames or sparks. Spark- and explosion proof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2 Environmental precautions:

Dam up the solid spill. Use appropriate containment to avoid environmental contamination.

6.3 Methods and material for containment and cleaning up:

Allow product to solidify and remove it by mechanical means. Carefully collect the spill/leftovers. Clean (treat) contaminated surfaces with acetone. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4 Reference to other sections:

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1 Precautions for safe handling:

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities:

Reason for revision: 2.2 Publication date: 2002-08-21
Date of revision: 2013-04-23

Revision number: 0401 Product number: 38450 4 / 15

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Unauthorized persons are not admitted. Meet the legal requirements. Max. storage time: 1 year(s).

7.2.2 Keep away from:

Heat sources, ignition sources, (strong) acids, (strong) bases, amines.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3 Specific end use(s):

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters:

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

ıne	Netherlands	٠

Dimethylether	Short time value	783 ppm 1500 mg/m ³	Public occupational exposure limit value
	Time-weighted average	e exposure limit 8 h 496 ppm 950 mg/m³	Public occupational exposure limit value

EU

Dimethylether	Time-weighted averag	e exposure	limit 8 h	1000 ppm 1920 mg/m	ndicative occupational exposure limit value

Belgium

Oxyde de diméthyle	Time-weighted average exposure		1000 ppm 1920 mg/m³	
Hydrocarbures aliphatiques gazeuse: (Alcanes C1-C4)	Time-weighted average exposure	e limit 8 h	1000 ppm	
	Time-weighted average exposure	e limit 8 h	1000 ppm	

USA (TLV-ACGIH)

Germany					
Butane, all isomers	Time-weighted averag	e exposur	re limit 8 h	1000 ppm	TLV - Adopted Value

Germany			_
Isobutan	Time-weighted average expos	osure limit 8 h 1000 ppm TRGS 900 2400 mg/m³	
Dimethylether	Time-weighted average expos	osure limit 8 h 1000 ppm TRGS 900 1900 mg/m³	
Propan	Time-weighted average expos	osure limit 8 h 1000 ppm TRGS 900 1800 mg/m ³	

France

110100					
Oxyde de diméthyle	Time-weighted average	je exposure li	imit 8 h	1000 ppm	VRI: Valeur réglementaire indicative
				1920 mg/m ³	

UK

•					
Isocyanates, all (as -NCO)	Except methyl	Short time value		0.07 mg/m³	Workplace exposure limit (EH40/2005)
isocyanate					1
		Time-weighted averag	e exposure limit 8 h	0.02 mg/m ³	Workplace exposure limit (EH40/2005)
Dimethyl ether		Short time value		500 ppm 958 mg/m³	Workplace exposure limit (EH40/2005)
		Time-weighted averag		400 ppm 766 mg/m³	Workplace exposure limit (EH40/2005)

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

Reason for revision: 2.2	Publication date: 2002-08-21
	Date of revision: 2013-04-23

Revision number: 0401 Product number: 38450 5 / 15

Product name	Test	Number
Isocyanates	NIOSH	5521
Isocyanates	NIOSH	5522
Methylene Bisphenyl Iso <mark>cyanate</mark>	OSHA	47

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL - Workers

tris(2-chloro-1-methylethyl) phosphate

Effect level (DNEL/DMEL)		Туре	Value	Remark
DNEL		Acute systemic effects dermal	0.528 mg/kg bw/day	
		Acute systemic effects inhalation	0.93 mg/m³	
		Long-term systemic effects dermal	0.528 mg/kg bw/day	
		L <mark>ong-term systemic effec</mark> ts inhalation	0.93 mg/m³	

DNEL - General population

tris(2-chloro-1-methylethyl) phosphate

Effect level (DNEL/DMEL)		Туре	Value	Remark
DNEL		<mark>Acute systemic effects de</mark> rmal	0.264 mg/kg bw/day	
		Acute systemic effects inhalation	0.23 mg/m ³	
		Acute -systemic effects oral	0.33 mg/kg bw/day	
		L <mark>ong-term systemic effect</mark> s dermal	0.264 mg/kg bw/day	
		L <mark>ong-term systemic effec</mark> ts inhalation	0.23 mg/m³	
		L <mark>ong-term systemic effec</mark> ts oral	0.33 mg/kg bw/day	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2 Exposure controls:

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

Materials	Breakthrough time Thickness	
LDPE (Low Density Poly Et <mark>hylene)</mark>	10 minutes	0.025 mm

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical form	Aerosol Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	No data available
Explosion limits	No data available
Flammability	Extremely flammable aerosol.
Log Kow	No data available
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available

Reason for revision: 2.2 Publication date: 2002-08-21
Date of revision: 2013-04-23

Revision number: 0401 Product number: 38450 6 / 15

Boiling point	No data available
9.1	No data available
Flash point	
Evaporation rate	No data available
Vapour pressure	No data available
Relative vapour density	>1
Solubility	water; insoluble
	organic solvents ; soluble
Relative density	0.95
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
рН	No data available

Physical hazards

Flammable aerosol

9.2 Other information:

Surface tension	No data ava	<mark>la</mark> ble
Absolute density	950 kg/m³	

SECTION 10: Stability and reactivity

10.1 Reactivity:

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2 Chemical stability:

Stable under normal conditions.

10.3 Possibility of hazardous reactions:

May polymerize with many compounds e.g.: (strong) bases and amines. Reacts violently with (some) acids/bases.

10.4 Conditions to avoid:

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5 Incompatible materials:

(strong) acids, (strong) bases, amines.

10.6 Hazardous decomposition products:

On heating: release of toxic/combustible gases/vapours (hydrogen cyanide). On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

11.1.1 Test results

Acute toxicity

Soudafoam Gun Low Expansion

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of	Parameter	Method	Value	Exposure t	ime Species	Gender	Value
exposure							determination
Oral	LD50	Equivalent 401	to OECD 1011-182 bw	24 mg/kg	Rat	Male/female	Experimental value
Dermal	LD50	OECD 402	> 2000 m	g/kg bw 24 h	Rabbit	Male/female	Experimental value
Inhalation (aerosol)	LC50	Equivalent 403	to OECD > 5 mg/l a	air 4 h	Rat	Male/female	Weight of evidence

polymethylene polyphenyl isocyanate

Route of	Parameter	Method	Value	Exposure time	Species	Gender	Value
exposure							determination
Oral	LD50		<mark>> 10000 m</mark> g/kg		Rat		Literature study
Dermal	LD50		> 5000 mg/kg		Rabbit		Literature study
Inhalation (vapours)	LD50		10-20 mg/l	4 h			Literature study

Reason for revision: 2.2 Publication date: 2002-08-21
Date of revision: 2013-04-23

Revision number: 0401 Product number: 38450 7 / 15

Classification of the mixture is based on the relevant ingredients of the mixture

Conclusion

Harmful if inhaled.

Low acute toxicity by the dermal route

Low acute toxicity by the oral route

Corrosion/irritation

Soudafoam Gun Low Expansion

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination
Eye		Equivalent to OECD 405	72 h	24; 48; 72 hours	Rabbit	Experimental value
Skin	Not irritating	OECD 404	4 h		Rabbit	Experimental value

polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination
Eye	Irrita <mark>ting</mark>					Literature study
Skin	Irritat <mark>ing</mark>					Literature study
Inhalation	Irrita <mark>ting</mark>					Literature study

Classification of the mixture is based on the relevant ingredients of the mixture

Conclusion

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

Specific target organ toxicity, single exposure: classified as irritant to respiratory organs

Respiratory or skin sensitisation

Soudafoam Gun Low Expansion

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of ex	xposure Result	Method	 Observation time point	Species	Value determination
Skin	Not sensi <mark>tizing</mark>	OECD 429		Mouse	Experimental value

polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Observation time point	Species	Value determination
Skin	Sensitizin <mark>g</mark>				Literature study
Inhalation	Sensitizing		-		Literature study

Classification of the mixture is based on the relevant ingredients of the mixture

Conclusion

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Specific target organ toxicity

Soudafoam Gun Low Expansion

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	 Value determination
Oral	LOAEL	Equivalent to OECD 408	800 ppm	Liver	Weight gain	13 weeks (daily)	Rat	Experimental value
Oral	NOAEL	Equivalent to OECD 408	2500 ppm		No effect	13 weeks (daily)	Rat	Experimental value

polymethylene polyphenyl isocyanate

iyinctifyiche polypi	ichtyr 130c yuriu	t <u>c</u>						
Route of	Parameter	Method	Value	Organ	Effect	Exposure time	Species	 Value
exposure								determination
Inhalation			STOT RE cat.2		1			Literature study

Classification of the mixture is based on the relevant ingredients of the mixture

Conclusion

May cause damage to organs through prolonged or repeated exposure if inhaled.

Low sub-chronic toxicity by the dermal route

Low sub-chronic toxicity by the oral route

Reason for revision: 2.2	Publication date: 2002-08-21
	Date of revision: 2013-04-23

Revision number: 0401 Product number: 38450 8 / 15

Mutagenicity (in vitro)

Soudafoam Gun Low Expansion

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Result	Method	Test substrate	Effect	Value determination
Negative		Chinese hamster lung fibroblasts	No effect	Weight of evidence
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Weight of evidence
Negative	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Weight of evidence

Mutagenicity (in vivo)

Soudafoam Gun Low Expansion

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Result	Method	Exposure time	Test substrate	Gender	Organ	Value determination
Negative	Equivalent to OECD 475		Rat	Male		Weight of evidence

Carcinogenicity

Soudafoam Gun Low Expansion

No (test)data on the mixture available

polymethylene polyphenyl isocyanate

		7							
Route of	Parameter	Method	Value	Exposure time	Species	Gender	Value	Organ	Effect
exposure							determination		
Inhalation			category 2		Rat		Literature study		Neoplastic
(aerosol)									effects

Reproductive toxicity

Soudafoam Gun Low Expansion

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

	Parameter	Method		Exposure time	Species	Gender	Effect	- 3	Value determination
Developmental toxicity	Loael (P)	OECD 416	3 3	>10 weeks (daily)	Rat		Body weight, organ weight, food consumption		Experimental value
	Noael (P)	OECD 416	85 mg/kg bw	>10 weeks (daily)	Rat	Male	No effect		Experimental value
		Equivalent to OECD 414	1000 mg/kg bw	70 day(s)	Rat	Female	No effect		Experimental value

Classification of the mixture is based on the relevant ingredients of the mixture

Conclusion CMR

Not classified for reprotoxic or developmental toxicity

Not classified for mutagenic or genotoxic toxicity

Suspected of causing cancer.

Toxicity other effects

Soudafoam Gun Low Expansion

No (test)data on the mixture available

Chronic effects from short and long-term exposure

Soudafoam Gun Low Expansion

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Feeling of weakness. Itching. Skin rash/inflammation. May stain the skin. Dry skin. Coughing. Possible inflammation of the respiratory tract. Respiratory difficulties.

11.1.2 Other information

Soudafoam Gun Low Expansion

EC carc cat	3	
CLP carc cat	category 2	

Reason for revision: 2.2 Publication date: 2002-08-21
Date of revision: 2013-04-23

 Revision number: 0401
 Product number: 38450
 9 / 15

polymethylene polyphenyl isocyanate

MAK - Krebserzeugend Kategorie

EC carc cat 3

CLP carc cat category 2

IARC - classification 3 (Polymethylene polyphenyl isocyanate)

SECTION 12: Ecological information

12.1 Toxicity:

Soudafoam Gun Low Expansion

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

	Parameter	Method	Value	Duration	Species	3	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		56.2 mg/l	96 h	Brachydanio rerio	Static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EC50	OECD 202	<mark>65 -</mark> 335 mg/l	48 h	Daphnia magna			Experimental value; GLP
Toxicity algae and other aqu <mark>atic</mark> plants	EC50	OECD 201	73 mg/l	96 h	Selenastrum capricornutum			Experimental value; Growth rate

polymethylene polyphenyl isocyanate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity other aquatic organisms	LC50		>1000 mg/l	96 h				Literature study
Toxicity aquatic micro- organisms	EC50	OECD 209	>100 mg/l		Activated sludge			Literature study

Classification of the mixture is based on the relevant ingredients of the mixture

Conclusion

No data available on ecotoxicity

12.2 Persistence and degradability:

tris(2-chloro-1-methylethyl) phosphate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301E: Modified OECD Screening Test	14 %	28 day(s)	Experimental value
OECD 301C: Modified MITI Test (I)	0 %	28 day(s)	Experimental value

polymethylene polyphenyl isocyanate

Biodegradation water

Method	Value	Duration	Value determination
OECD 302C: Inherent Biodegradability:	< 60 %		Experimental value
Modified MITI Test (II)			

Conclusion

Contains non readily biodegradable component(s)

12.3 Bioaccumulative potential:

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

tris(2-chloro-1-methylethyl) phosphate

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.8 - 4.6		Cyprinus carpio	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
		2.59		Experimental value

Reason for revision: 2.2 Publication date: 2002-08-21
Date of revision: 2013-04-23

Revision number: 0401 Product number: 38450 10 / 15

polymethylene polyphenyl isocyanate

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		1		Pisces	Literature study

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

No bioaccumulation data available

12.4 Mobility in soil:

No (test)data on mobility of the components of the mixture available

12.5 Results of PBT and vPvB assessment:

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

12.6 Other adverse effects:

Soudafoam Gun Low Expansion

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No. 1272/2008 and 1005/2009)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1 Waste treatment methods:

13.1.1 Provisions relating to waste

Waste material code (Directive 2008/98/EC, decision 2000/0532/EC).

08 04 09* (waste adh<mark>esives and sealants containing organic</mark> solvents or other dangerous substances). Depending on branch of industry and production process, also other EURAL codes may be applicable. Hazardous waste according to Directive 2008/98/EC.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Specific treatment. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Reason for revision: 2.2

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

oad (ADR)	
14.1 UN number:	
UN number	1950
14.2 UN proper shipping name:	
Proper shipping name	Aerosols
14.3 Transport hazard class(es):	
Hazard identification nu <mark>mber</mark>	
Class	2
Classification code	5F
14.4 Packing group:	
Packing group	
Labels	2.1
14.5 Environmental hazards:	
Environmentally hazardous substance mark	no
14.6 Special precautions for user:	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass)

Revision number: 0401 Product number: 38450 11 / 15

Publication date: 2002-08-21 Date of revision: 2013-04-23

ail (RID)	
14.1 UN number:	
UN number	1950
14.2 UN proper shipping name:	
Proper shipping name	Aerosols
14.3 Transport hazard class(es):	
Hazard identification number	23
Class	2
Classification code Classification code	5F
14.4 Packing group:	
Packing group	
Labels	2.1
14.5 Environmental hazards:	
Environmentally hazard <mark>ous substance mark</mark>	no
14.6 Special precautions for user:	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
nland waterways (ADN) 14.1 UN number:	
UN number	1950
14.2 UN proper shipping name:	
Proper shipping name	Aerosols
14.3 Transport hazard class(es):) to cools
Class	2
Classification code	5F
14.4 Packing group:	
Packing group	
Labels	2.1
14.5 Environmental hazards:	E 1
Environmentally hazardous substance mark	no
14.6 Special precautions for user:	lio
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg. (gross mass)
ea (IMDG)	
14.1 UN number:	
UN number	1950
14.2 UN proper shipping name:	
Proper shipping name	Aerosols
14.3 Transport hazard class(es):	
Class	2.1
14.4 Packing group:	
Packing group	
Labels	2.1
14.5 Environmental hazards:	
Marine pollutant	
Environmentally hazard <mark>ous substance mark</mark>	no
14.6 Special precautions for user:	
Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
on for revision: 2.2	Publication date: 2002-08-21

Revision number: 0401 Product number: 38450 12 / 15

Soudafoam Gun Low Expansion 959 Special provisions Limited quantities Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code. Annex II of MARPOL 73/78 Not applicable, based on available data Air (ICAO-TI/IATA-DGR) 14.1 UN number: UN number 1950 14.2 UN proper shipping name: Aerosols, flammable Proper shipping name 14.3 Transport hazard class(es): Class 14.4 Packing group: Packing group 2.1 Labels 14.5 Environmental hazards Environmentally hazardous substance mark no 14.6 Special precautions for user: A145 Special provisions Special provisions A167 A802 Special provisions Passenger and cargo tra<mark>nsport: limited quantities: maximum n</mark>et quantity 30 kg G

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

European legislation:

per packaging

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group substances or of the mixture	f Conditions of restriction
tris(2-chloro-1-methylethyl) phosph polymethylene polyphenyl isocyana	regarded as dangerous according to the	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and iokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304,4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).5. Without prejudice to the implementation of other Community provisions relating to the classification packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are packaged ir black opaque containers not exceeding 1 litre by 1 December 2010. 6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils ar grill lighte
propane isobutane dimethyl ether	Substances meeting the criteria of flammatin Directive 67/548/ EEC and classified as flammable, highly flammable or extremely flammable regardless of whether they appein Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	ility 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs.2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 sha not apply to the aerosol dispensers referred to Article 8 (1a) of Council
son for revision: 2.2		Publication date: 2002-08-21

Revision number: 0401 Product number: 38450 13 / 15

Date of revision: 2013-04-23

		Directive 75/ 324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) including the following specific isomers: 4,4'- Methylenediphenyl diisocyanate; 2,4'- Methylenediphenyl diisocyanate; 2,2'- Methylenediphenyl diisocyanate	Shall not be placed on the market after 27 December 2010, as a constituent of mixtures in concentrations equal to or greater than 0,1 % by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging: (a) contains protective gloves which comply with the requirements of Council Directive 89/686/EEC; (b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures: "— Persons already sensitised to diisocyanates may develop allergic reactions when using this product. — Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. — This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used."2. By way of derogation, paragraph 1(a) shall not apply to hot melt adhesives.

Volatile organic compounds (VOC)

20 %

National legislation

- The Netherlands

Waterbezwaarlijk <mark>heid</mark>	8
Waterbezwaarlijk <mark>heid</mark>	
Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 06

- Germany

WGK	1 Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)		
TALC	1	Th. (14) 505	
TA-Luft	propane	TA-Luft Klasse 5.2.5	
TA-Luft	isobutane	TA-Luft Klasse 5.2.5	
TA-Luft	dimethyl ether	TA-Luft Klasse 5.2.5	

MAK (Germany)

WIAK (Ochhany)				
Dimethylether		Time-weighted average exposure limit 8 h	1000 ppm 1900 mg/m³	
"polymeres MDI"	(einatembare Fraktion)	Time-weighted average exposure limit 8 h		E: gemessen als einatembare Fraktion (vgl. Abschn. Vd) S. 191)
Propan		Time-weighted average exposure limit 8 h	1000 ppm 1800 mg/m ³	
Butan (beide Ison	neren)	Time-weighted average exposure limit 8 h	1000 ppm 2400 mg/m ³	

15.2 Chemical safety assessment:

No chemical safety assessment has been conducted.

SECTION 16: Other information

Full text of any R-phrases referred to under headings 2 and 3:

R20 Harmful by inhalation

R22 Harmful if swallowed

R36/37/38 Irritating to eyes, respiratory system and skin

R40 Limited evidence of a carcinogenic effect

R42/43 May cause sensitisation by inhalation and skin contact

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

Full text of any H-statements referred to under headings 2 and 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

DSD Dangerous Substance Directive
DPD Dangerous Preparation Directive

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

Reason for revision: 2.2 Publication date: 2002-08-21
Date of revision: 2013-04-23

Revision number: 0401 Product number: 38450 14 / 15

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.



Date of revision: 2013-04-23

15 / 15 Revision number: 0401 Product number: 38450